

PRODUCT DATA SHEET

Ansell Lighting APRILEDP/MINI/CCT



Prism Pro Mini

Manufacturer: Ansell Lighting

GTIN: 5056144259052

Family: [Display]

Range: Prism Pro Mini Fire Rated



DESCRIPTION

Ultra-slim, angled remote LED driver with push-fit terminals for easy install. Fits shallow ceiling voids. Detachable for fast fixing. Use solo or with Prism Pro/Anti-Glare. Compliant with Parts B, C, E & L of Building Regs. Ideal for 30, 60 & 90 min ceiling types.

- Ultra slim remote driver with loop-in, loop-out push fit terminals provide an easy and efficient installation
- Ultra slim remote driver with loop-in, loop-out push fit terminals provide an easy and efficient installation
- Can be used as the sole light source or as a complimentary product to Prism Pro / Prism Pro Anti-Glare
- Unique angled LED driver for easy installation through the smaller downlight cut out
- Detachable LED driver for fast fix install
- Low profile design and arched remote driver allows installation into shallow ceiling voids
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

TECHNICAL SPECIFICATION

ETIM Class: Downlight / spot luminaire / floodlight (EC001744)



Primary Features

Colour of light	White	Maximum system power (W)	5
Colour temperature (K)	2700 - 6000	Nominal voltage (V)	220 - 240
Light source included	Yes	Number of lamps	1

Additional Features

Adjustability	Not adjustable	Suitable for pedestal/floor mounting	No
Beam angle	Wide beam 40-80°	Suitable for recessed mounting	Yes
Colour consistency (McAdam ellipse)	SDCM6	Suitable for surface mounting	No
Colour rendering index (CRI/Ra)	80-89	Suitable for suspended mounting	No
Control gear included	Yes	Suitable for traverse mounting	No
Height/depth (mm)	57	Suitable for wall mounting	No
Outer diameter (mm)	55	Unified Glare Rating (UGR)	29
Protection class according to IEC 61140	II	With light sensor	No
Suitable for ceiling mounting	Yes	With movement sensor	No
Suitable for light-track mounting	No		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405119090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.