

PRODUCT DATA SHEET

Airflow 72683501

100mm iCON15 (Boxed)

Manufacturer: Airflow Developments Limited

GTIN: 5019009307633

Family: Domestic fans

Range: iCON



DESCRIPTION

iCON 15 is ideal for toilets, en-suites, shower rooms and bathrooms. Recessed into the wall or ceiling, it is stylish and unobtrusive, even in the smallest space. The quiet axial fan has been designed with simplicity in mind. A quick, core drilled hole enables immediate fixing of iCON 15. The twist on/off cover requires only a single side entry fixing screw. Cantilever fixing lugs enable recessed installation on uneven surfaces. The optional 'snap-in' module is quick to fit and wire. Tiling is a breeze with the circular cover flange, reducing the need to 'make good' and one wipe and the cover is clean. Stylish, slim and unobtrusive in walls or ceilings. Unique iris shutter, prevents back draughts, operates silently and helps reduce noise ingress. Interchangeable control modules match fan to installation requirements. Splash proof, tiling friendly, wipe clean cover. Fan operates by remote switch (optional). No module required. Please note: Model above is for basic on/off switching. Choose an optional control module to upgrade fan for Pullcord, Timer, Humidity or Motion Sensing operation. Don't forget to add the control module you want. Any module fits any fan. Its so iCON easy!

Applications Toilet, En-suite and Bathrooms

- Flow rate up to 19 l/sec (68 m3/hr)
- Ductable for short runs. Silent shutter
- Stylish design
- Low energy, quiet in use
- Complies with latest Building Regulations (F1 ventilation)
- Choice of optional control
- Wall/ceiling, recessed mounting
- Upgrade your cover colour to match décor
- 3 year warranty

TECHNICAL SPECIFICATION

ETIM Class: Ventilator for in-house bathrooms and kitchens (EC001141)



Primary Features

Colour	White	Height (mm)	197
Degree of protection (IP rating)	Other	Nominal width (mm)	100
Depth (mm)	108.5	Width (mm)	197

Additional Features

Assembly	Standard	Medium temperature (°C)	0 - 40
Direction	Axial	Mounting method	Surface mounted/recessed mounted
Flow rate (m³/h)	68	Nominal current (A)	0.05
Housing material	Plastic	Rated voltage (V)	240
Mains frequency (Hz)	60		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 07-05-2025

Trade Tariff Commodity Code: Not supplied

Country of Origin: Not supplied

Airflow Developments Limited, Aidelle House, Lancaster Road, Cressex Business Park, High Wycombe, HP12 3QP

☎ 01494 525252

✉ info@airflow.com

🌐 <https://www.airflow.com/>

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 12/12/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.