PRODUCT DATA SHEET

Ansell Lighting APAC1/60/1

Pace Backlit CCT Multi Wattage 600x600 Panel UGR<19

Manufacturer: Ansell Lighting

GTIN: 5056687310814

Family: [Commercial]

Range: Pace CCT MultiWattage 600x600 UGR<19



DESCRIPTION

Backlit LED panel with slimline design allows for installation into shallow ceiling voids. CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire.

- Backlit LED panel suitable for education, commercial and ancilary area applications
- Slimline design allows for installation into shallow ceiling voids
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort
- Dimmable and OCTO options available
- TPa as standard
- Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC
- Compatible with either the self-test panel pod or the sensor pod

TECHNICAL SPECIFICATION

ETIM Class: Ceiling / wall luminaire (EC002892)

Primary Features

Colour of light	White	Light source type	LED non-replaceable
Housing colour	White	Maximum system power (W)	30
Light source included	Yes	Voltage type	AC

Additional Features

Beam angle	Extreme wide beam >80°	Length (mm)	595
Beam angle adjustable	No	Light diffuser type	Diffuser
Bluetooth operated	No	Light distribution	Symmetric
Colour consistency (McAdam ellipse)	SDCM3	Light outlet	Direct
Colour rendering index (CRI/Ra)	80-89	Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	80
Colour temperature switchable	Discrete positions	Lumen setting adjustable	No
Compatible with Amazon Alexa	No	Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Compatible with Apple HomeKit	No	Power factor	9
Compatible with Google Assistant	No	Protection class according to IEC 61140	II
Constant luminous flux control	No	Rated life time L70/B50 at 25 °C (h)	60000
Control gear included	Yes	Replaceable control gear	Yes
Cover material	Plastic opal	Suitable for ceiling mounting	No
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	50	Suitable for emergency lighting	No
Fit for workplace acc. EN 12464-1	Yes	Suitable for surface mounting	No
Housing material	Aluminium	Suitable for suspended mounting	No
Housing surface protection	Untreated	Type of cabling	Ending
IFTTT support available	No	Unified Glare Rating (UGR)	19

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405119090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD
01942 433 333 saleswarrington@anselluk.com http://www.anselluk.com

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.