

# PRODUCT DATA SHEET

## Ansell Lighting ADIS2/2

### Disco EVO 2 XPRESS



Manufacturer: Ansell Lighting

GTIN: 5056687333059

Family: Bulkheads

Range: Disco EVO



## DESCRIPTION

Disco EVO 2 Xpress ADIS2/2 Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas, High efficiency up to 145lm/W, All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories, CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire, Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation, Updated to work with Xpress Emergency & Microwave sensors, Instant light output and unlimited switching. IP65. Material: Polycarbonate,PP. Finish: White. Wattage: 8 - 16W W. Lumens: (4000K) 9W: 1200lm 12W: 1800lm 16W: 2300lm lm. Colour temperature: 3000/4000/6500K K. CRI: 80. Operating temperature: -20°C - 40°C.

- Slim and modern bulkhead suitable for residential, commercial and industrial applications as well as ancillary areas
- Compatible with XPRESS emergency and microwave sensors
- High efficiency up to 145lm/W
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome, satin chrome or graphite trim ring accessories
- CCT selectable between 3000K, 4000K and 6500K and power selectable; offering a choice of 3 outputs, in one luminaire
- Gear tray located on the bezel, allowing the base to be installed and then the bezel connected, this coupled with 4x 20mm conduit entry points on base ensure a quick and simple installation
- Updated to work with XPRESS Emergency & Microwave sensors
- Instant light output and unlimited switching

- Built in spirit level for ease of installation with horizontal conduit

## TECHNICAL SPECIFICATION



### ETIM Class: Ceiling / wall luminaire (EC002892)

#### Primary Features

|                                       |        |                     |                     |
|---------------------------------------|--------|---------------------|---------------------|
| Degree of protection (IP), front side | IP65   | Light source type   | LED non-replaceable |
| Housing colour                        | White  | Nominal voltage (V) | 220 - 240           |
| Lamp power (W)                        | 8 - 16 |                     |                     |

#### Additional Features

|                                     |                        |                                         |     |
|-------------------------------------|------------------------|-----------------------------------------|-----|
| Beam angle                          | Extreme wide beam >80° | Outer diameter (mm)                     | 325 |
| Colour consistency (McAdam ellipse) | SDCM3                  | Protection class according to IEC 61140 | II  |
| Colour rendering index (CRI/Ra)     | 80-89                  | Suitable for ceiling mounting           | Yes |
| Cover material                      | Plastic opal           | Suitable for emergency lighting         | No  |
| Height/depth (mm)                   | 85                     | Suitable for wall mounting              | Yes |
| Housing material                    | Plastic                | Unified Glare Rating (UGR)              | 26  |
| Impact resistance (IK rating)       | IK08                   |                                         |     |

## FURTHER DETAILS

Product Status (at download): Active

Date Updated: 01-07-2026

Trade Tariff Commodity Code: 9405114090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

#### Disclaimer

- This Data Sheet was downloaded from EDATA - [www.edata.org.uk](http://www.edata.org.uk) - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/07/2026.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.