

PRODUCT DATA SHEET

Ansell Lighting AMALL2/1



Matrix 2 Linklight

Manufacturer: Ansell Lighting

GTIN: 5056687304745

Family: [Display]

Range: Matrix



DESCRIPTION

CCT Selectable LED linklight with integral driver suitable for residential and retail applications. Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options and moulded spine fitted with integral switch and fixed diffuser.

- CCT Selectable LED linklight with integral driver suitable for residential and retail applications
- Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options
- Moulded spine fitted with integral switch and fixed diffuser
- c/w angled and straight fixing clips
- Supplied with 230V 1.5m mains power lead and linking plug adaptor
- End-to-end linking provides aesthetically pleasing seamless light output
- Linkable up to a maximum of twelve fittings
- Non-dimmable

TECHNICAL SPECIFICATION

ETIM Class: Ceiling / wall luminaire (EC002892)



Primary Features

Colour of light	White	Light source type	LED non-replaceable
Housing colour	White	Maximum system power (W)	5
Light source included	Yes	Voltage type	AC

Additional Features

Beam angle	Extreme wide beam >80°	Length (mm)	300
Beam angle adjustable	No	Light diffuser type	Diffuser
Bluetooth operated	No	Light distribution	Asymmetric
Colour consistency (McAdam ellipse)	SDCM6	Light outlet	Direct
Colour rendering index (CRI/Ra)	80-89	Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	80
Colour temperature switchable	No	Lumen setting adjustable	No
Compatible with Amazon Alexa	No	Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Compatible with Apple HomeKit	No	Power factor	5
Compatible with Google Assistant	No	Protection class according to IEC 61140	II
Constant luminous flux control	No	Rated life time L70/B50 at 25 °C (h)	60000
Control gear included	No	Replaceable control gear	No
Cover material	Plastic opal	Suitable for ceiling mounting	No
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	50	Suitable for surface mounting	Yes
Fit for workplace acc. EN 12464-1	No	Suitable for suspended mounting	No
Height/depth (mm)	37	Type of cabling	Ending
Housing material	Plastic	Unified Glare Rating (UGR)	22
Housing surface protection	Untreated	Width (mm)	23
IFTTT support available	No		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405423100

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

**Disclaimer**

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 17/11/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.